ULTRATECH 10W30 SP

Code: 1204
Date: 30-11-2023

DESCRIPTION

ULTRATECH 10W30 SP is a mineral low-viscosity oil designed for the latest gasoline direct-injected (GDI) engines providing engine protection as well as enhanced fuel economy. It meets the latest API SP requirements and provides the highest protection against sludge, deposits, valve train wear and catalytic converter fouling and LSPI unique to GDI engines.

SUMMARY OF BENEFITS

- 10W30 SP offers outstanding control of cam wear.
- Better piston cleanliness and excellent engine sludge protection
- Excellent control of oxidation and oil loss due to volatility
- Better high temperature wear protection
- Fully compatible with prior ILSAC and API categories
- LSPI protection in GDI engines

SPECIFICATIONS

- API SP. SN PLUS (RC)
- ILSAC GF-6A, GF-5
- CHRYSLER MS 6395

SUITABLE FOR USE – OUTSIDE OF WARRANTY

API SN/CF, SM/CF, SL/CF

TECHNICAL DATA

CHARACTERISTICS	10W30 SP
Specific gravity at 15 C	0.864
Kinematic viscosity at 40 C, mm2/s (cSt)	68.3
Kinematic viscosity at 100 C, mm2/s (cSt)	11.2
Viscosity index	157

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED