ULTRATECH 25W70 SJ/CF-4

Code: 1650
Date: 10-04-2017

DESCRIPTION

ULTRATECH 25W70 SJ/CF-4 is a high viscosity oil made from a unique blend of additives to produce ideally suited to older vehicles and worn engines. It is developed to provide sealing and wear protection on older engines that have looser clearances. It is able to resist thinning and shearing even under severe conditions.

SUMMARY OF BENEFITS

ULTRATECH 25W70 SJ/CF-4 is recommended for all turbo charged passenger vehicles both diesel and petrol, and is highly desirable for the following applications:

- High performance local and imported cars.
- Racing inboard power boats.
- Off road recreational vehicles.
- All 4-Stroke motorcycles including Harley Davidson.
- Wet Clutch applications and where oil is subject to very high temps
- Vehicles using both leaded and unleaded fuel.

SPECIFICATIONS

- API SJ/CF-4
- SAE Viscosity 25W70

TECHNICAL DATA

CHARACTERISTICS	25W70 SJ/CF4
Specific gravity at 15 C	0.908
Kinematic viscosity at 40 C, mm2/s (cSt)	250
Kinematic viscosity at 100 C, mm2/s (cSt)	27.0
Viscosity index	141.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED