

4 STROKE SAE 30

Code: 1830 Date: 10-03-2017

DESCRIPTION

FOUR STROKE SAE 30 Oil is formulated for use in crankcases of small four stroke petrol engines. It is recommended for use in four stroke outdoor power equipment such as lawn mowers, stationary engines, generator sets, ride-on mowers, compact tractors, rotary hoes, industrial blowers and vacuums where an SAE 30 engine oil is specified. FOUR STROKE SAE 30 Oil is red in colour and is suitable in most Briggs & Stratton, Honda, Kohler and Robin engines.

SUMMARY OF BENEFITS

FOUR STROKE SAE 30 is a cost-efficient oil for lawnmower engines and others requiring API SG/CD performance levels. It will control oil consumption and deposits and contains anti wear additives along with rust and oxidation inhibitors. Four Stroke SAE 30 Oil is suitable for use with unleaded and lead replacement fuels.

SPECIFICATIONS

- SAE 30
- API SG/CD

TECHNICAL DATA

CHARACTERISTICS	4 STROKE SAE 30
Specific gravity at 15 C	0.864
Kinematic viscosity at 40 C, mm2/s (cSt)	95.0
Kinematic viscosity at 100 C, mm2/s (cSt)	10.5
Viscosity index	92.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C



