TWO STROKE TC

Code: 1900
Date: 25-04-2015

DESCRIPTION

2-STROKE is a low ash high performance two stroke engine oil, suitable for use in all two stroke engines in lawn mowers, brush cutters and chainsaws and other power equipment. It can also be used in motorcycle engines requiring API TC performance levels.

SUMMARY OF BENEFITS

2-STROKE should be used in conjunction with the engine manufacturers recommendation regarding fuel/oil ratio, however, in the absence of such information a 50 to 1 fuel/oil ratio is advised

2-STROKE is not recommended for water-cooled two-stroke marine outboards

SPECIFICATIONS

- JASO FC
- API TC
- ISO-L-EGC
- TISI 1040-2534
- BIS T-SL4

TECHNICAL DATA

CHARACTERISTICS	TWO STROKE TC
Specific gravity at 15 C	0.8650
Kinematic viscosity at 40 C, mm2/s (cSt)	58.0
Kinematic viscosity at 100 C, mm2/s (cSt)	8.9
Viscosity index	129
Colour	Green

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED