



# SUPER OUTBOARD TCW III

Code: 1950

Date: 25-04-2015

## DESCRIPTION

**SUPER OUTBOARD OIL** is a premium low smoke engine oil formulated with an ashless additive system, designed for all water cooled two stroke outboard engines including oil injected and pre-mix systems. SUPER OUTBOARD OIL is self-mixing and suitable for oil injection systems often fitted to modern two stroke outboards.

## SUMMARY OF BENEFITS

Approved by the National Manufacturers Association (NMMA) for service TC-W3  
Superior friction and wear control.

SUPER OUTBOARD OIL should be mixed according to the ratio recommended by the manufacturer. It can be used at fuel/oil ratios of up to 100/1 however, 50/1 ratio is advised in the absence of engine recommendations.

## SPECIFICATIONS

Suitable for all outboard two stroke engines operating on leaded or unleaded petrol with or without injection lubrication

- EVINRUDE
- MERCURY
- YAMAHA
- TOHATSU
- JOHNSON
- FORCE
- SUZUKI
- MARINER

## TECHNICAL DATA

CHARACTERISTICS	SUPER OUTBOARD TCW 3
Specific gravity at 15 C	0.8716
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	50.3
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	7.5
Viscosity index	110
Colour	Blue

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

**TRITECH LUBRICANTS AND SALES PTY LTD**  
151 Colemans Road, Dandenong South VIC 3175  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)  
Phone: 1300 46 33 33

