

## DESCRIPTION

**DEXRON III** is a transmission fluid designed for use in automatic transmissions where Dexron® III or Dexron® II fluids have been specified. This product is a high viscosity index fluid containing superior additive technology and greatly improved low temperature properties for smooth cold shifts.

## SUMMARY OF BENEFITS

- Excellent seal compatibility
- Oxidation control
- Anti-wear and friction performance
- Also used as a power steering fluid

## SPECIFICATIONS

- DEXRON IIIH
- DEXRON IIIIG
- DEXRON IIIIF
- FORD MERCON
- ALLISON C-4
- CATERPILLAR TO-2
- M2C138-CJ
- M2C166-H
- POWER STEERING

## TECHNICAL DATA

CHARACTERISTICS	ATF DEXRON 3
Specific gravity at 15 C	0.8660
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	41.5
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	8.1
Viscosity index	173

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C