

## DESCRIPTION

**ATF UNIVERSAL** is the latest generation in automatic transmission fluid technology, and has been developed to cover a wide range of specific vehicle applications. **ATF UNIVERSAL** utilizes premium highly stable mineral base oil and new generation automatic transmission fluid additive technology to improve transmission durability, shift performance and minimize transmission shudder. It provides excellent oxidation and thermal stability resulting in superior wear protection.

## SUMMARY OF BENEFITS

- Anti shudder durability for smooth shifting performance
- Enhanced wear protection

## SPECIFICATIONS

- HONDA Z1
- ALLISON C-4
- ZF TE-ML-14A
- VOLVO 97341
- VOITH H55.6335.XX
- MAN 339 TYPE V-1, Z-1
- MITSUBISHI SP-II AND SP-III
- MB, VW AND BMW 4 AND 5 SPEED AUTOMATICS.
- JASO 1-A
- TOYOTA T-III, T-IV
- FORD MERCON V
- NISSAN MATIC D & J

## TECHNICAL DATA

| CHARACTERISTICS  | UNIVERSAL |
|--|-----------|
| Specific gravity at 15 C                               | 0.8673    |
| Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)  | 41.30     |
| Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt) | 8.0       |
| Viscosity index  | 170.0     |
| Colour   | RED       |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C