

DESCRIPTION

POWERTRANS FLUIDS are high performance, multifunctional transmission fluids blended from premium base oils and selected additives designed to meet the requirements of Allison, Caterpillar and Komatsu final drives, powershift transmissions, torque converters, hydraulic systems, off-highway equipment and any other system calling for TO-4 specification.

SUMMARY OF BENEFITS

- Superior gear wear protection
- Improved power transfer efficiency
- Excellent thermal stability

SPECIFICATIONS

- API CF / CF-2
- ALLISON C-4
- CATERPILLAR TO-4M
- CATERPILLAR TO-4
- KOMATSU

TECHNICAL DATA

CHARACTERISTICS	POWERTRANS 10
Specific gravity at 15 C	0.8662
Kinematic viscosity at 40 C, mm ² /s (cSt)	37.00
Kinematic viscosity at 100 C, mm ² /s (cSt)	6.10
Viscosity index	110.00

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

