POWERTRANS 10W TO -4

Code: 3710
Date: 04-03-2021

DESCRIPTION

POWERTRANS FLUIDS are high performance, multifunctional transmission fluids blended from premium base oils and selected additives designed to meet the requirements of Allison, Caterpillar and Komatsu final drives, powershift transmissions, torque converters, hydraulic systems, off-highway equipment and any other system calling for TO-4 specification.

SUMMARY OF BENEFITS

- Superior wear protection and load carrying capacity
- Improved power transfer efficiency
- Excellent friction control and performance
- Elastomer compatibility
- Excellent thermal and oxidation stability
- Outstanding yellow metal protection
- Suitable for wet brakes

SPECIFICATIONS

- SAE 10W
- ALLISON C-4
- EATON FULLER
- API MT-1
- CATERPILLAR TO-4M
- CATERPILLAR TO-4
- CATERPILLAR TO-2
- KOMATSU KES 07.868.1
- VICKERS M-2950-S
- ZF TE-ML-03C / 07F

TECHNICAL DATA

CHARACTERISTICS	POWERTRANS 10W
Specific gravity at 15 C	0.8662
Kinematic viscosity at 40 C, mm2/s (cSt)	37.00
Kinematic viscosity at 100 C, mm2/s (cSt)	6.10
Viscosity index	110.00

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED