



# POWERTRANS 50WTO-4

Code: 3750  
Date: 27-01-2016

## DESCRIPTION

**POWERTRANS FLUIDS** are high performance, multifunctional transmission fluids blended from premium base oils and selected additives designed to meet the requirements of Allison, Caterpillar and Komatsu final drives, powershift transmissions, torque converters, hydraulic systems, off-highway equipment and any other system calling for TO-4 specification.

## SUMMARY OF BENEFITS

- Superior gear wear protection
- Improved power transfer efficiency
- Excellent thermal stability

## SPECIFICATIONS

- API CF / CF-2
- ALLISON C-4
- CATERPILLAR TO-4M
- CATERPILLAR TO-4
- KOMATSU

## TECHNICAL DATA

CHARACTERISTICS	POWERTRANS 50
Specific gravity at 15 C	0.8865
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	188
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	17.8
Viscosity index	103

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)

