GEAR LUBE S/S 75W80 GL-4

Code: 4002
Date: 20-04-2016

DESCRIPTION

GEAR LUBE SS 75W80 GL-4 is a high viscosity index, semi synthetic manual gearbox lubricant containing sophisticated extreme pressure additives and base oils. It is designed to give maximum protection to transaxles and gearboxes operating under the most arduous conditions.

.

SUMMARY OF BENEFITS

- Smooth shift
- Enhanced oxidation stability
- Semi Synthetic for longer life
- Superior wear protection

SPECIFICATIONS

- API GL-4
- CHRYSLER MS 9224
- MB 235.10
- LAND ROVER MTF 94
- ZF TE-ML 02D
- HONDA MTF 7289

TECHNICAL DATA

CHARACTERISTICS	GEAR OIL 75W80 GL-4 SEMI SYN
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm2/s (cSt)	55.0
Kinematic viscosity at 100 C, mm2/s (cSt)	9.80
Viscosity index	165

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED