GEAR LUBE 75W90 GL-5

Code: 4003
Date: 30-10-2020

DESCRIPTION

GEAR LUBE 75W90 GL-5 is an extreme pressure multi grade manual gearbox lubricant offering superior wear protection and excellent low temperature characteristics designed to give maximum protection to gearboxes, differentials (hypoid and spiral), transfer cases and transaxles in cars, light commercial vehicles, 4WDs, trucks, construction equipment, agricultural equipment and other applications.

SUMMARY OF BENEFITS

- Smooth shift
- Enhanced oxidation stability
- Suitable for most 4 and 5 speed manual transmissions
- Superior wear protection

SPECIFICATIONS

- API GL-5
- MT-1
- MACK GO-J

TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE 75W90 GL-5
Specific gravity at 15 C	0.8690
Kinematic viscosity at 40 C, mm2/s (cSt)	105
Kinematic viscosity at 100 C, mm2/s (cSt)	15.2
Viscosity index	152

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED