

# GEAR LUBE 80W90 GL-5

Code: 4004 Date: 30-05-2020

#### DESCRIPTION

**GEAR LUBE 80W90 GL-5** is an extreme pressure multi grade manual gearbox lubricant offering superior wear protection and excellent low temperature characteristics designed to give maximum protection to gearboxes, differentials (hypoid and spiral), transfer cases and transaxles in cars, light commercial vehicles, 4WDs, trucks, construction equipment, agricultural equipment and other applications.

## **SUMMARY OF BENEFITS**

- Smooth shift
- Enhanced oxidation stability
- Suitable for most 4 and 5 speed manual transmissions
- Superior wear protection

### **SPECIFICATIONS**

- API GL-5
- MT-1
- CHRYSLER MS-9020
- MIL-L 2105D

# **TECHNICAL DATA**

| CHARACTERISTICS                           | GEAR LUBE 80W90 GL5 |
|---|---------------------|
| Specific gravity at 15 C                  | 0.8770              |
| Kinematic viscosity at 40 C, mm2/s (cSt)  | 155                 |
| Kinematic viscosity at 100 C, mm2/s (cSt) | 15.3                |
| Viscosity index                           | 99                  |

• Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

**TRITECH LUBRICANTS AND SALES PTY LTD** 151 Colemans Road, Dandenong South VIC 3175 Web: www.tritechlubricants.com Phone: 1300 46 33 33

#### CASE INTERNATIONAL BOS 9001:2015 REGISTERNATIONAL BOS 9001:2015 REGISTERNATIONAL BOS 9001:2015



AUSTRALIAN MADE AND AUSTRALIAN OWNED