

## DESCRIPTION

**GEAR LUBE LS 90 GL-5** is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers to reduce and prevent squeal in limited slip differentials.

## SUMMARY OF BENEFITS

- Protects from heavy loads and shock loading
- Advanced friction modifiers to reduce squeal
- Provides smooth power take up
- Superior wear protection and seal compatibility

## SPECIFICATIONS

- API GL-5, GL-5 LS
- SAE J2360
- MACK GO-J

## TECHNICAL DATA

| CHARACTERISTICS  | GEAR LUBE LS90 GL5 |
|--|--------------------|
| Specific gravity at 15 C                               | 0.890              |
| Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)  | 170                |
| Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt) | 17.0               |
| Viscosity index  | 110                |

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C