GEAR LUBE
LS90 GL-5

Code: 4006
Date: 15-08-2020

DESCRIPTION

GEAR LUBE LS 90 GL-5 is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without “limited slip” design. It contains extreme pressure additives and special friction modifiers to reduce and prevent squeal in limited slip differentials.

.

SUMMARY OF BENEFITS

- Protects from heavy loads and shock loading
- Advanced friction modifiers to reduce squeal
- Provides smooth power take up
- Superior wear protection and seal compatibility

SPECIFICATIONS

- API GL-5, GL-5 Limited Slip (LS)
- SAE J2360
- MACK GO-J

TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE LS90 GL5
Specific gravity at 15 C	0.890
Kinematic viscosity at 40 C, mm2/s (cSt)	170
Kinematic viscosity at 100 C, mm2/s (cSt)	17.0
Viscosity index	110

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED