



GEAR OIL 85W140 GL5

Code: 4007
Date: 30-05-2018

DESCRIPTION

85W140 GL5 is an extreme pressure multi grade differential and gearbox lubricant offering superior wear protection and excellent low temperature characteristics designed to give maximum protection to gearboxes and differentials.

SUMMARY OF BENEFITS

- 85W140 GL5 is designed for use in differentials in passenger cars, light commercial vehicles, trucks and agricultural equipment and is formulated to give maximum protection even in severe operating conditions.

SPECIFICATIONS

- API GL5
- US STEEL 224
- 51517 PART III:
- MACK GO – H
- MIL-L-2105E

TECHNICAL DATA

CHARACTERISTICS	GEAR OIL 85W140 GL5
Specific gravity at 15 C	0.8960
Kinematic viscosity at 40 C, mm ² /s (cSt)	380
Kinematic viscosity at 100 C, mm ² /s (cSt)	27.3
Viscosity index	97

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

