

## DESCRIPTION

**GEAR LUBE 85W140 GL-5** is a heavy extreme pressure multi grade differential lubricant offering superior wear protection and good low temperature characteristics designed to give maximum protection to gearboxes and differentials in heavy loads and shock-loading. It is also suitable in gearboxes in some trucks where this oil grade is recommended.

## SUMMARY OF BENEFITS

- Protects differentials, final drives and axles from heavy loads and shock loading
- High temperature stability and oxidation resistance
- Superior wear protection
- Recommended for heavy duty applications like 4WDs, trucks, trailers, farm machinery, construction equipment and other heavy applications.

## SPECIFICATIONS

- API GL-5
- MT-1
- CHRYSLER MS-9020
- MIL-L 2105D

## TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE 85W140 GL-5
Specific gravity at 15 C	0.8960
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	351
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	26.2
Viscosity index	99

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C