



GEAR OIL 85W140 GL-5

Code: 4007

Date: 13-04-2018

DESCRIPTION

GEAR OIL 85W140 GL-5 is a heavy extreme pressure multi grade differential and gearbox lubricant offering superior wear protection and good low temperature characteristics designed to give maximum protection to gearboxes and differentials in heavy loads and shock-loading.

SUMMARY OF BENEFITS

- Protects differentials, final drives and axles from heavy loads and shock loading
- High temperature stability and oxidation resistance
- Superior wear protection
- Recommended for heavy duty applications like 4WDs, trucks, trailers, farm machinery, construction equipment and other heavy applications.

SPECIFICATIONS

- API GL-5
- MT-1
- CHRYSLER MS-9020

TECHNICAL DATA

| CHARACTERISTICS | GEAR OIL 85W140 GL-5 |
|--|----------------------|
| Specific gravity at 15 C | 0.8960 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 380 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 28.0 |
| Viscosity index | 102 |

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

