

## DESCRIPTION

**GEAR LUBE LS 140 GL-5** is a thick extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid differentials both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers to reduce squeal and protect against heavy and shock loads.

## SUMMARY OF BENEFITS

- Protects differentials, final drives and axles from heavy loads and shock loading
- High temperature stability and oxidation resistance and seal compatibility
- Offers superior wear protection, prevents squeals and provides smooth take off.
- Recommended for heavy duty applications like 4WDs, trucks, trailers, farm machinery, construction equipment and other heavy applications.

## SPECIFICATIONS

- API GL-5, GL-5 LS
- SAE J2360
- MACK GO-J

## TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE LS140 GL-5
Specific gravity at 15 C	0.911
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	389
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	27.3
Viscosity index	95.4

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C