HYDRAULIC OIL ISO: 32

Code: 5002
Date: 21-01-2018

DESCRIPTION

HYDRAULIC OIL 32 is a premium hydraulic oil, containing high quality zinc anti-wear additives and rust and corrosion inhibitors. HYDRAULIC OIL 32 promotes superior performance in oxidation protection, water tolerance, thermal stability and pump durability.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties
- Excellent wear protection

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MACHINE P-68, P-69, P-70
- EATON BROCHURE 694 for 35VQ25A
- DIN 51524 Part 2 (HLP)
- GM LS2
- ISO 11158 Categories HM
- ASTM D 6158 Type HM
- AFNOR NF E 48-603 HM

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 32
Specific gravity at 15 C	0.860
Kinematic viscosity at 40 C, mm2/s (cSt)	32
Kinematic viscosity at 100 C, mm2/s (cSt)	5.6
Viscosity index	125

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED