

## DESCRIPTION

**SUPERDRAULIC HVI 46** is a premium performance anti-wear hydraulic oil, made with high viscosity index improvers designed to maintain close viscosity control over wide temperature range applications.

## SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties
- Wide temperature range

## SPECIFICATIONS

- DENISON TP02100
- VICKERS 1-286-S
- DIN 51524 Part 2 (HLP)
- US STEEL 126 & 127
- AFNOR NF E 48-603 HM and HL

## TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC HVI ISO: 46
Specific gravity at 15 C	0.862
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	46
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	8.4
Viscosity index	150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)

