BRAKE FLUID DOT 3

Code: 6015
Date: 08-07-2018

DESCRIPTION

BRAKE FLUID DOT 3 is a high performance polyglycol-based brake fluid designed for use in a wide range of brake and clutch applications where DOT 3 specifications is called for. BRAKE FLUID DOT 3 has a higher than normal boiling point and low volatility and is recommended for re-fill or top-up of brake and clutch systems in passenger cars, light and heavy commercial vehicles, four wheel drives, tractors and motorcycles. DO NOT use where DOT 4 brake fluid is recommended. DO NOT mix with DOT 5.0 brake fluids.

SUMMARY OF BENEFITS

BRAKE FLUID DOT 3 can be used for disc or drum brake and clutch systems and is developed to meet Australian and International standards.
Boiling point exceeds Australian Standards for safe braking even during extreme driving conditions. Excellent flowability even in very cold conditions for safe braking in freezing conditions. Compatible will rubber and other seals in modern brake systems.

SPECIFICATIONS

- US FMVSS 116 DOT 3
- ISO 4925
- SAE J1703
- AS 1960.1 GRADE 1

TECHNICAL DATA

CHARACTERISTICS	TYPICAL	SPECIFICATION
BOILING POINT °C (MIN DRY ERBP)	243	230
BOILING POINT °C (MIN WET ERBP)	151	140
KINEMATIC VISCOSITY @ -40°C, cSt	1270	1500 max
@ 100°C cSt	2.2	1.5 min
DENSITY @20°C, g/ml	1.031	NOT REQUIRED

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED