

DESCRIPTION

COMPRESSOR OIL 46 is an air compressor lubricant formulated from highly refined base oils and state of the art non-hydrolyzing anti wear additives developed for rotary screw compressors. The result is a finished product which has long life, protects compressor components from wear and which also separates readily from water. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C. Drain intervals can be extended to up to 4000 hours in rotary screw compressors where an oil test program is in place.

SUMMARY OF BENEFITS

- Long drain intervals
- Zinc-free anti-wear protection
- Robust rust and oxidation inhibitors
- Ash-free formulation

SPECIFICATIONS

- ISO / DP 6521 DAH, DAG
- DIN 51506 VBL, VCL, VDL

TECHNICAL DATA

| CHARACTERISTICS | COMPRESSOR 46 |
|--|---------------|
| Specific gravity at 15 C | 0.8500 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 46.0 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 7.0 |
| Viscosity index | 110.0 |

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C