COMPRESSOR OIL
ISO: 46

Code: 7011
Date: 06-09-2023

DESCRIPTION

COMPRESSOR OIL 46 is an air compressor lubricant formulated from highly refined hydrotreated base oils and state of the art non-hydrolysing anti wear additives developed for screw compressors. The result is a finished product which has long service life while protecting compressor components from wear. Critically, it also separates readily from water to facilitate more effective corrosion protection. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C. Also suitable for hydraulic, turbine and gearbox applications especially where an ashless lubricant is a requirement.

SUMMARY OF BENEFITS

- Long drain intervals and excellent filterability
- Zinc-free anti-wear protection, hydrolytic stability, water separability
- Robust rust and oxidation inhibitors
- Ash-free formulation
- Corrosion protection for steel and copper parts

SPECIFICATIONS

- DP 6521 DAH, DAG, DAA. DAB
- DIN 51506 (VBL, VCL, VDL)
- BB HTG 90117
- MIL-L-17672 D
- DIN 51524 Part1 (R&O), 2 (HLP, AW)
- AFNOR NF E 48-603
- CIN. MILACRON P38, P54, P55, P57, P62
- DENISON HF-0, HF-1, HF-2

TECHNICAL DATA

CHARACTERISTICS	COMPRESSOR 46
Specific gravity at 15 C	0.8500
Kinematic viscosity at 40 C, mm2/s (cSt)	46.0
Kinematic viscosity at 100 C, mm2/s (cSt)	7.0
Viscosity index	110.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED