



COMPRESSOR OIL

ISO: 68

Code: 7012
Date: 06-09-2019

DESCRIPTION

COMPRESSOR OIL 68 is an air compressor lubricant formulated from highly refined base oils and state of the art non-hydrolyzing anti wear additives developed for screw and reciprocating air compressors. The result is a finished product which has long life, protects compressor components from wear and also separates readily from water. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C.

SUMMARY OF BENEFITS

- Long drain intervals
- Zinc-free anti-wear protection
- Robust rust and oxidation inhibitors
- Ash-free formulation

SPECIFICATIONS

- ISO / DP 6521 DAH, DAG
- DIN 51506 VBL, VCL, VDL

TECHNICAL DATA

CHARACTERISTICS	COMPRESSOR OIL 68
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm ² /s (cSt)	68.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	9.1
Viscosity index	109.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

