



INDUSTRIAL GEAR OIL ISO: 320

Code: 7024
Date: 10-05-2016

DESCRIPTION

IGO 320 is a premium quality, heavy duty industrial gear lubricant manufactured from highly refined base stocks and extreme pressure additives. Designed for use in all types of industrial gear boxes and can also be used in sprockets, chain drives and slide guides.

SUMMARY OF BENEFITS

- Excellent demulsibility
- Protects against rust and corrosion
- Good oxidation and thermal stability for long life
- Particularly suited for steel on bronze industrial worm gears.

SPECIFICATIONS

- DAVID BROWN S1.53.101E
- AGMA 250.04, 9005-D94
- DIN 51 517 (PART 3)
- U.S STEEL 224
- API GL-3

TECHNICAL DATA

CHARACTERISTICS	IGO 320
Specific gravity at 15 C	0.890
Kinematic viscosity at 40 C, mm ² /s (cSt)	320
Kinematic viscosity at 100 C, mm ² /s (cSt)	26.0
Viscosity index	106.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS

15 Leah Grove, Carrum Downs, Victoria, Australia 3201
 Phone: +61 3 9708 2317, Fax: +61 3 9708 2318
 Email: sales@tritechlubricants.com,
 Web: www.tritechlubricants.com,



AUSTRALIAN MADE AND
AUSTRALIAN OWNED