

DESCRIPTION

SLIDEWAY 68 is recommended for high precision lathes, cutting machines, planers and other similar equipment that have slideways. It prevents chatter and stick-slip in slideways and also serves to lubricate bearings and gears. **SLIDEWAY 68** is also fortified with tackifiers to reduce sling off and improve performance.

SUMMARY OF BENEFITS

SLIDEWAY 68 will adhere to the working surfaces especially in both horizontal and vertical slideways under high load and temperature and resist wash out from water soluble cutting fluids. It is fortified with additives to protect equipment from wear and corrosion.

SPECIFICATIONS

- ISO 68
- Cincinnati Milacron: P47

TECHNICAL DATA

CHARACTERISTICS	SLIDEWAY 68
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm ² /s (cSt)	68
Kinematic viscosity at 100 C, mm ² /s (cSt)	10.0
Viscosity index	128

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

