SLIDEWAY OIL ISO: 68

Code:7080
Date: 13-08-2022

DESCRIPTION

SLIDEWAY OIL 68 is recommended for high precision lathes, cutting machines, planers and other similar equipment that have slideways. It has a unique lubricity additive that prevents chatter and stick-slip in slideways for smoother movement of slides. SLIDEWAY OIL 68 is also fortified with tackifiers to reduce sling off and improve performance and promotes adhesion to vertical surfaces of cutting machines.

SUMMARY OF BENEFITS

SLIDEWAY OIL 68 will adhere to the working surfaces especially in both horizontal and vertical slideways under high load and temperature and resist wash out from water soluble cutting fluids. It is fortified with EP and anti-wear additives to protect equipment from wear and corrosion.

SPECIFICATIONS

- ISO 68
- Cincinnati Milacron: P47
- US Steel 224

TECHNICAL DATA

CHARACTERISTICS	SLIDEWAY 68
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm2/s (cSt)	68
Kinematic viscosity at 100 C, mm2/s (cSt)	9.62
Viscosity index	121

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED