SLIDEWAY OIL ISO: 220

Code:7083
Date: 09-09-2019

DESCRIPTION

SLIDEWAY OIL 220 is recommended for high precision lathes, cutting machines, planers and other similar equipment that have slideways. It prevents chatter and stick-slip in slideways and also serves to lubricate bearings and gears. SLIDEWAY OIL 220 is also fortified with tackifiers to reduce sling off and improve performance.

SUMMARY OF BENEFITS

SLIDEWAY OIL 220 will adhere to the working surfaces especially in both horizontal and vertical slideways under high load and temperature and resist wash out from water soluble cutting fluids. It is fortified with additives to protect equipment from wear and corrosion.

SPECIFICATIONS

- ISO 220
- Cincinnati Milacron: P47

TECHNICAL DATA

CHARACTERISTICS	SLIDEWAY 220
Specific gravity at 15 C	0.880
Kinematic viscosity at 40 C, mm2/s (cSt)	220
Kinematic viscosity at 100 C, mm2/s (cSt)	19.5
Viscosity index	113

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED