CUTTING OIL NEAT 31

Code: 7120
Date: 11-09-2019

DESCRIPTION

CUTTING OIL NEAT 31 is a low viscosity extreme pressure mineral non-soluble cutting oil with low odour characteristics for machine operator's comfort. It contains an extreme pressure additive system, rust and anti-foam additives for long tool life, good heat transfer and surface finish.

SUMMARY OF BENEFITS

- Chlorine free
- Low viscosity
- Compatible with all metals
- Non staining on ferrous and non-ferrous metals
- Easily removed in end-product applications.
- Longer tool life

APPLICATIONS

CUTTING OIL NEAT 31 is designed for high speed machining such as cutting, drilling, broaching of steel, stainless steel, aluminium, copper and other alloys.

TECHNICAL DATA

CHARACTERISTICS	CUTTING OIL NEAT 31
Specific gravity at 15 C	0.8650
Kinematic viscosity at 40 C, mm2/s (cSt)	32.0
Kinematic viscosity at 100 C, mm2/s (cSt)	5.6
Viscosity index	114.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED