



NEATCUT CUTTING OIL 68

Code: 7120

Date: 11-09-2019

DESCRIPTION

NEATCUT CUTTING OIL is an extreme pressure mineral non-soluble cutting oil with low odour characteristics for machine operator's comfort. It is heavier so its use is confined to heavier operations such as gear cutting, broaching, turning, threading and tapping. It contains an extreme pressure additive system, rust and anti-foam additives for long tool life, good heat transfer and surface finish.

SUMMARY OF BENEFITS

- Chlorine free
- Compatible with all metals
- Non staining on ferrous and non-ferrous metals
- Easily removed in end product applications.
- Longer tool life

APPLICATIONS

NEATCUT CUTTING OIL is designed for lower speed machining with heavier cuts such as gear cutting, drilling, broaching of steel, stainless steel, aluminium, copper and other alloys.

TECHNICAL DATA

CHARACTERISTICS	NEATCUT CUTTING OIL
Specific gravity at 15 C	0.8660
Kinematic viscosity at 40 C, mm ² /s (cSt)	68.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	8.5
Viscosity index	94.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

