LITHTAC RED GREASE EP2

Code: 8110
Date: 03-05-2018

DESCRIPTION

LITHTAC RED GREASE EP2 is a premium, heavy duty EP grease ideally suited for applications in which heavy shock loading is encountered. The heavy viscosity base oils and tackifiers make this grease ideal. The tackifier ensures the grease will stay where it is applied and is suitable for automotive and industrial equipment operating in wet, muddy or dusty conditions

SUMMARY OF BENEFITS

LITHTAC RED GREASE EP2 can also be used in rolling contact bearings in electrical motors, blowers, centrifugal pumps etc where a high-quality grease is desired. Also used in rolling contact and plain sleeve bearings used in unfavourable environmental conditions involving moisture, high loads and or high temperatures, such as jaw crushers, tube mills, mining, material processing, cement and aggregate industries.

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM
TEXTURE	SMOOTH/TACKY
COLOUR	RED
DROPPING POINT °C	195 min
FOUR BALL WELD LOAD, KGS	315
BASE OIL CHARACTERISTICS	
BASE OIL VISCOSITY @40°C cST	450
OPERATING TEMPERATURE RANGE °C	-20 to 150
NLGI GRADE	2

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED