



LITHTAC RED GREASE EP2

Code: 8110

Date: 03-05-2018

DESCRIPTION

LITHTAC RED GREASE EP2 is a premium, heavy duty EP grease ideally suited for applications in which heavy shock loading is encountered. The heavy viscosity base oils and tackifiers make this grease ideal. The tackifier ensures the grease will stay where it is applied and is suitable for automotive and industrial equipment operating in wet, muddy or dusty conditions

SUMMARY OF BENEFITS

LITHTAC RED GREASE EP2 can also be used in rolling contact bearings in electrical motors, blowers, centrifugal pumps etc where a high quality grease is desired. Also in rolling contact and plain sleeve bearings used in unfavourable environmental conditions involving moisture, high loads and or high temperatures, such as jaw crushers, tube mills, mining, material processing, cement and aggregate industries.

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM
TEXTURE	SMOOTH/TACKY
COLOUR	RED
DROPPING POINT °C	195 min
FOUR BALL WELD LOAD, KGS	315
BASE OIL CHARACTERISTICS	
BASE OIL VISCOSITY @40°C cST	450
OPERATING TEMPERATURE RANGE °C	-20 to 150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
 Phone: 1300 46 33 33, Email: info@tritechlubricants.com
 Web: www.tritechlubricants.com



AUSTRALIAN MADE AND AUSTRALIAN OWNED