

DESCRIPTION

LITHTAC EP2 is a premium, heavy duty EP grease ideally suited for applications in which heavy shock loading is encountered. The combination of polymers and heavy viscosity base oils and tackifiers make this grease ideal. The polymer ensures the grease will stay where it is applied and is suitable for automotive and industrial equipment operating in wet, muddy or dusty conditions

SUMMARY OF BENEFITS

LITHTAC EP2 can also be used in rolling contact bearings in electrical motors, blowers, centrifugal pumps etc where a high quality grease is desired. Also in rolling contact and plain sleeve bearings used in unfavourable environmental conditions involving moisture, high loads and or high temperatures, such as jaw crushers, tube mills, mining, material processing, cement and aggregate industries.

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM
TEXTURE	SMOOTH/TACKY
COLOUR	RED
DROPPING POINT D-2265 F MIN	350
TIMKEN OK LOAD, ASTM D-2509, LB MIN	60
BASE OIL CHARACTERISTICS	
VISCOSITIES:	
@ 100 C, cST	26.0-28.5
@ 40 C, cST	390-450
@ 100 F, SUS	2100-2300
VISCOSITY INDEX	85

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

