

## DESCRIPTION

**LITHPLEX EP2** is a premium lithium complex lubricating grease containing a tackiness agent. This universal lithium complex grease has a high dropping point in excess of 260°C, which ensures retention where high temperatures are encountered. It offers significant advantages over conventional soap and clay based greases in terms of shear stability, thermal stability, water resistance and pumpability.

## SUMMARY OF BENEFITS

**LITHPLEX EP2** has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties. The high quality virgin base fluids provide excellent natural oxidation inhibition. This combined with effective anti-oxidants as well as corrosion inhibitors provide extra stability under storage and extreme service conditions.

## SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM COMPLEX
TEXTURE	SMOOTH/TACKY
COLOUR	BLUE
DROPPING POINT D-2265 F (C) MIN	500 (260)
TIMKEN OK LOAD, D-2509, LB	60
<b>BASE OIL CHARACTERISTICS</b>	
VISCOSITIES:	
@ 100 C, cST	16.5-19.0
@ 40 C, cST	180-240
@ 210 F, SUS	86.0-96.0
@ 100 F, SUS	925-1250
VISCOSITY INDEX, MIN	90

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
**Phone:** 1300 46 33 33, **Email:** [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
**Web:** [www.tritechlubricants.com](http://www.tritechlubricants.com)

