MOLYLITH BLACK GREASE EP2

Code: 8130
Date: 03-05-2018

DESCRIPTION

MOLYLITH BLACK GREASE EP2 is a lubricating grease formulated to meet the extreme conditions encountered on off- highway construction equipment as well as heavy duty applications. This product is a Lithium Complex thickened grease blended with high viscosity base fluids for exceptional film strength and is fortified with 3% molybdenum disulphide for additional load carrying capacity and anti-wear performance.

SUMMARY OF BENEFITS

MOLYLITH BLACK GREASE EP2 is ideal for wet environments and better performance at high temperatures. Because it is lithium complex thickened grease, MOLYLITH BLACK GREASE EP2 has a high dropping point which also provides excellent protection in high temperature environments. Ideally suited for Truck and Farm applications

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM COMPLEX
TEXTURE	TACKY
COLOUR	GREY/BLACK
DROPPING POINT °C	250 MIN
FOUR BALL WELD LOAD, KGS	500
BASE OIL VISCOSITY @40°C	460
OPERATING TEMPERATURE RANGE °C	-20 to 150

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED