

DESCRIPTION

SYNTECH 10W40 SN SEMI SYN is a multi functional premium semi synthetic petrol/diesel oil developed for passenger cars manufactured from 1980. Formulated and blended to achieve a superior level of engine protection meeting the very latest API technology. Developed to reduce oil consumption and has excellent circulation capabilities due to its high viscosity index enabling it to protect the engine during cold temperature start up operation.

SUMMARY OF BENEFITS

SYNTECH 10W40 SN offers excellent flow and pumpability on cold start, Semi synthetic providing fuel saving capability and very low oil consumption due to low volatility.

SYNTECH 10W40 SN meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG

SPECIFICATIONS

- API SN/CF
- VW 502.00, 505.00
- ACEA A3/B4
- FORD ESE-M2C 153E
- JASO VTW

TECHNICAL DATA

CHARACTERISTICS	SYNTECH 10W40 SN/CF
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm ² /s (cSt)	94.5
Kinematic viscosity at 100 C, mm ² /s (cSt)	13.9
Viscosity index	150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

