



SYNERGY 5W30 SN/CF

Code: 9180
Date: 10-05-2016

DESCRIPTION

SYNERGY 5W30 is a full synthetic petrol/diesel energy conserving motor oil which provides the highest level of protection from combustion deposits, heat induced oil oxidation and sludge deposits. **SYNERGY 5W30** is a multi viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts. **SYNERGY 5W30** provides protection against wear and corrosion, prevents oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits.

SUMMARY OF BENEFITS

SYNERGY 5W30 meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines

SYNERGY 5W30 maintains outstanding engine cleanliness

SPECIFICATIONS

- VW 502.00, 505.00
- FORD M2C946-A
- ACEA A3/B4
- API SN
- MB –APPROVAL 229.5
- BMW LONGLIFE- 01
- PORSCHE

TECHNICAL DATA

CHARACTERISTICS	5W30 SN/CF
Specific gravity at 15 C	0.854
Kinematic viscosity at 40 C, mm ² /s (cSt)	67
Kinematic viscosity at 100 C, mm ² /s (cSt)	11.2
Viscosity index	161

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

