

## DESCRIPTION

**SYNERGY 5W30** is a full synthetic petrol/diesel motor oil formulated with advanced synthetic base stocks and a premium additive. It has a broad viscosity range providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals. SYNERGY 5W30 is a low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts. It also provides protection against wear and corrosion, prevents oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits.

## SUMMARY OF BENEFITS

SYNERGY 5W30 meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines

## SPECIFICATIONS

- API SN / CF / CF-2
- ACEA A3/B3, A5/B5
- BMW LL-O/M54
- DAIMLER CHRYSLER MS 6395K
- GM dexos 1
- MB 229.1, 229.5
- MIL-L-2104B
- MIL-L-46152
- LAND ROVER
- PSA B 71 2300
- RENAULT 0700
- VW 50200, 50300, 50500, 50600

## TECHNICAL DATA

CHARACTERISTICS	5W30 SN/CF
Specific gravity at 15 C	0.854
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	67
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	11.2
Viscosity index	161

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C