



SYNERGY EURO SYN 5W30 E4/E6 LOW SAPS

Code: 9243

Date: 10-07-2016

DESCRIPTION

SYNERGY EURO E4/E6 is a fully synthetic ultra high performance heavy duty diesel engine oil. It meets and complies with the demanding requirements of Euro 4 exhaust emission legislation. **SYNERGY EURO E4/E6** is ideally designed for European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3 and Euro 4 Exhaust emission legislation.

SUMMARY OF BENEFITS

- Full Synthetic Formulation
- Suitable for use where particulate filters are used
- Outstanding low temperature viscometrics for reduced wear at start up.
- Low SAPS (Sulfated Ash, Phosphorous and Sulfur)
- Super extended drain intervals surpassing any mineral or American diesel type lubricant.
- Reduces fuel consumption due to superior technology.
- Excellent soot and sludge control resulting in cleaner engines

SPECIFICATIONS

- API CJ-4
- MAN 3477/3575/3271-1
- MB228.51
- ACEA E4/E6/E7/E9
- CATERPILLAR ECF-3
- DETROIT DIESEL 93K218
- MTU TYPE 3.1
- VOLVO VDS-4
- CUMMINS CES 20081
- DEUTZ DQC IV-10 LA
- RENAULT TRUCK RLD/RLD-2
- MACK EO-O PREMIUM PLUS

TECHNICAL DATA

CHARACTERISTICS	5W30 E4/E6 LOW SAPS
Specific gravity at 15 C	0.850
Kinematic viscosity at 40 C, mm ² /s (cSt)	64
Kinematic viscosity at 100 C, mm ² /s (cSt)	11.5
Viscosity index	178

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
 Phone: 1300 46 33 33, Email: info@tritechlubricants.com
 Web: www.tritechlubricants.com

