SYNERGY EURO 5W30 E6/E8

Code: 9243
Date: 21-07-2026

DESCRIPTION

SYNERGY EURO 5W30 E6/E8 is a full synthetic, energy-conserving, ultra-high-performance, heavy-duty diesel engine oil. It meets and complies with the demanding requirements of Euro 6 exhaust emission legislation. It is also backwards compatible to European engines meeting Euro I to Euro VI emission requirements and can be used in vehicles with or without after exhaust treatment devices like DPFs and SCRs. Formulated for extra-long drain intervals.

SUMMARY OF BENEFITS

- Low viscosity, full synthetic formulation
- Suitable for use where particulate filters are used
- Outstanding low temperature viscosity characteristics for reduced wear at start up
- Low SAPS (Sulphated Ash, Phosphorous and Sulphur)
- Super extended drain intervals surpassing any mineral or American diesel type lubricant
- Reduced fuel consumption with lower viscosity
- Excellent soot and sludge control resulting in cleaner engines
- High oil film strength even at extreme loads

SPECIFICATIONS

- ACEA E6/E8-22, E7-22/E11-22
- API CK-4
- MB 228.31/51/52 (DTFR 15C100/110/120)
- MAN 3775/ 3275 /3575 / 3677 / 3271-1
- ACEA E4 (suitable for use)
- RENAULT TRUCK RLD-3
- MTU TYPE 3.1 / 2.1
- SCANIA LOW ASH, LDF-4
- FORD WSS-M2C213-A
- MACK EO-S4.5, EO-O P PLUS 7
- VOLVO VDS 3, 4, 4.5
- CUMMINS CES 20081 / 20086
- DEUTZ DQC IV-18 LA, DQC IV-10 LA / DQC III-10 LA
- DAF PSQL 2.1E-LD
- JASO DH-1, DH-2, GLOBAL DHD-1
- CATERPILLAR ECF-3, ECF-2, ECF-1A
- DD DFS 93K222, 93K218, 7SE-270, 2000/4000 CAT-1

TECHNICAL DATA

CHARACTERISTICS	5W30 E6/E8
Specific gravity at 15 C	0.8500
Kinematic viscosity at 40 C, mm2/s (cSt)	72.3
Kinematic viscosity at 100 C, mm2/s (cSt)	11.95
Viscosity index	162

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED