SYNERGY EURO 5W40 C3

Code: 9282
Date: 10-10-2020

DESCRIPTION

SYNERGY EURO 5W40 C3 is designed for European engines requiring SHPD (Super High-Performance Diesel) level of performance and those which comply with the latest European exhaust emission legislation. SYNERGY EURO 5W40 C3 is a full synthetic mid SAPS formulation and is suitable for use where particulate filters are used. It also meets API SP and it is able to provide protection from LSPI which is inherent in the latest petrol GDI turbocharged engines.

SUMMARY OF BENEFITS

SYNERGY EURO 5W40 C3 provides excellent wear protection at start up and during high speeds and/or high loads.
SYNERGY EURO 5W40 C3 has excellent oxidation resistance and outstanding sludge control resulting in cleaner engines and longer drain intervals. Its low/mid SAPS formulation makes it suitable for use where DPFs are in use. Oil chemistry provides LSPI protection.

SPECIFICATIONS

- ACEA C3, C2 (SFU)
- API SP
- VW 502.00, 505.00, 505.01
- MB 229.31/ 229.51/ 226.5
- RENAULT RN0700 / 0710
- BMW LONGLIFE- 04
- GM DEXOS 2
- PORSCHE A40
- FORD WSS-M2C917-A
- DAIMLER CHRYSLER MS 6395K

TECHNICAL DATA

CHARACTERISTICS	5W40 C3
Specific gravity at 15 C	0.8580
Kinematic viscosity at 40 C, mm2/s (cSt)	92
Kinematic viscosity at 100 C, mm2/s (cSt)	14.8
Viscosity index	169

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED