



ATF SYN MULTITRANS

Code: 9350
Date: 28-05-2016

DESCRIPTION

SYN MULTI-TRANS is a new generation multipurpose, full synthetic Automatic Transmission Fluid developed to cover virtually all ATF specifications. With the exception of CVT transmissions and Ford "Type F" transmissions, **SYN MULTI-TRANS** is truly a one stop Automatic Transmission Fluid. Designed to meet Japanese, American and European transmissions, **SYN MULTI-TRANS** is the perfect choice for the consumer who does not want to carry multiple drums of product.

SUMMARY OF BENEFITS

SYN MULTI-TRANS is a very versatile fluid and can be used in almost all Japanese and many European and American vehicles as a service fill, and may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

SPECIFICATIONS

Full list of specifications available on request.

- ALLISON C-4
- AISN WARNER AW-1
- AUDI G 052 162, G 052 990, G 055 025
- BMW 83 22 0 142 516, 83 22 2 152 426
- CHRYSLER ATFs, MOPAR AS68RC
- DEX -II, IID, IIE,
- DEX -111H, IIIF, IIIG, -VI
- FORD FNRS, MERCON, MERCON V
- HONDA ATF-Z1
- HYUNDAI/KIA SP-II, SP-III, JWS 3314, JWS 3317
- MAN 339F, 339 V1, 339 Z1
- MAZDA ATF-M III, ATF-MV
- MERCEDES BENZ 236.1, 236.2, 236.3, 236.5,
- MITSUBISHI SP-II, SP-111, ATF J2
- NISSAN 402, MATIC-D, J, K, -S
- SHELL 3403, LA2634, M-1375.4, M-1375.5, M-1375.6, M-12108
- TOYOTA T, T-II, T-III, T-IV, WS-(JWS 3324)
- VW G 052 162, G 052 990, G 055 005, G 055 025, G 055 162, G060 162
- ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C

TECHNICAL DATA

CHARACTERISTICS	SYN MULTITRANS
Specific gravity at 15 C	0.847
Kinematic viscosity at 40 C, mm ² /s (cSt)	33.5
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.1
Viscosity index	182

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

