

DESCRIPTION

SYNGEAR LS 75W90 GL5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and low excellent low temperature characteristics due to its blend of selected synthetic base and advance extreme pressure additives. It is formulated to be suitable in limited slip differentials.

SUMMARY OF BENEFITS

SYNGEAR LS 75W90 GL5 is ideal for use in transaxles with combined manual gearbox, hypoid differentials and limited slip differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe of conditions. It is formulated for outstanding wear protection, seal compatibility, shear stability, and thermal and oxidation stability for extended oil service life. The excellent wear and corrosion protection it provides ensures extended equipment life.

SPECIFICATIONS

- API GL-4/GL-5, MT-1
- MILITARY SPECIFICATIONS MIL-PRF-2105E
- ZF TE-ML 07A, ZF TE-ML 08
- FORD- M2C 200C
- DAIMLER MS5630
- DANA 40819

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR LS 75W90 GL5
Specific gravity at 15 C	0.857
Kinematic viscosity at 40 C, mm ² /s (cSt)	110
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.8
Viscosity index	179

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C