SYNGEAR
LS 75W90 GL5

Code: 9410
Date: 19-07-2026

DESCRIPTION

SYNGEAR LS 75W90 GL5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and excellent low temperature characteristics due to its blend of selected synthetic base and advance extreme pressure additives. It is formulated to be suitable in limited slip differentials.

SUMMARY OF BENEFITS

SYNGEAR LS 75W90 GL5 is ideal for use in transaxles with combined manual gearbox, hypoid differentials and limited slip differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe of conditions. It is formulated for outstanding wear protection, seal compatibility, shear stability, and thermal and oxidation stability for extended oil service life. The excellent wear and corrosion protection it provides ensures extended equipment life.

SPECIFICATIONS

- API GL-4/GL-5, MT-1
- SAE J2360
- MACK GO-J / GO-J PLUS
- FORD- M2C 200-C
- SCANIA STO 1:0

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR LS 75W90 GL5
Specific gravity at 15 C	0.8553
Kinematic viscosity at 40 C, mm2/s (cSt)	94
Kinematic viscosity at 100 C, mm2/s (cSt)	14.9
Viscosity index	167

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED