



SYNGEAR LIMITED SLIP LS 80W-140 GL-5

Code: 9420
Date: 15-08-2016

DESCRIPTION

SYNGEAR LS 80W140 GL-5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and low excellent low temperature characteristics due to its blend of selected synthetic base and extreme pressure additives. It contains the Sturaco 7098 friction modifier for use in limited slip differentials that suffer from severe chatter.

SUMMARY OF BENEFITS

SYNGEAR LS 80W140 GL-5 is ideal for use in transaxles with combined manual gearbox and hypoid differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe of conditions.

SPECIFICATIONS

- MILITARY SPECIFICATIONS MIL-PRF-2105E
- ZF TE-ML 07A, ZF TE-ML 08
- FORD- M2C118-A
- DAIMLER MS5630
- DANA 40819
- ISO 12925-1 CKC/CKD
- DIN 51517 PART 3
- AGMA 9005-E02
- API GL5
- USS 224

TECHNICAL DATA

| CHARACTERISTICS | SYNGEAR LS 80W-140 GL-5 |
|--|-------------------------|
| Specific gravity at 15 C | 0.8550 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 300 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 33.5 |
| Viscosity index | 155 |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

