



HYDRAULIC OIL ISO: 15

Code: 5000
Date: 21-01-2016

DESCRIPTION

HYDRAULIC OIL 15 is a premium hydraulic oil, containing high quality zinc antiwear additives.

HYDRAULIC OIL 15 promotes superior performance in oxidation protection, water tolerance, thermal stability and pump durability.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MACHINE P-68, p-70, p-69
- EATON BROCHURE 694 for 35VQ25A
- DIN 51524 Part 2 (HLP) & Part 3 (HVLP)
- GM LS2
- ISO 11158 Categories HM and HV
- ASTM D 6158 Type HM and HV
- AFNOR NF E 48-603 HM and HV

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 15
Specific gravity at 15 C	0.830
Kinematic viscosity at 40 C, mm ² /s (cSt)	15
Kinematic viscosity at 100 C, mm ² /s (cSt)	3.5
Viscosity index	112

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

