HYDRAULIC OIL ISO: 22

Code: 5001
Date: 21-04-2024

DESCRIPTION

HYDRAULIC OIL 22 is a premium, low viscosity hydraulic oil blended with hydrocracked base oils and a state-of-the-art zinc-free anti-wear additive system. This special formulation ensures outstanding performance over a wide temperature range – ensuring good oil flow during cold days and outstanding wear protection in extremely hot days.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties
- Excellent wear protection

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MILACRON P-38, 54, 55, 57, 62
- MIL-L-176-72-D
- DIN 51524 Part1 & 2 (HLP)
- ISO 11158 Categories HM
- ASTM D 6158 Type HM
- AFNOR NF E 48-603 HM

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 22
Specific gravity at 15 C	0.850
Kinematic viscosity at 40 C, mm2/s (cSt)	22
Kinematic viscosity at 100 C, mm2/s (cSt)	4.6
Viscosity index	126

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED