



SUPER HYDRAULIC HVI 32

Code: 5102
Date: 25-08-2015

DESCRIPTION

SUPER HYDRAULIC HVI 32 is a premium performance anti-wear hydraulic oil, made with high viscosity index improvers designed to maintain close viscosity control over wide temperature range applications.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties

SPECIFICATIONS

- DENISON TP02100
- VICKERS 1-286-S
- DIN 51524 Part 2 (HLP)
- US STEEL 126 & 127
- AFNOR NF E 48-603 HM and HL

TECHNICAL DATA

CHARACTERISTICS	SUPER HYDRAULIC HVI ISO: 32
Specific gravity at 15 C	0.870
Kinematic viscosity at 40 C, mm ² /s (cSt)	32
Kinematic viscosity at 100 C, mm ² /s (cSt)	6.4
Viscosity index	150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS

15 Leah Grove, Carrum Downs, Victoria, Australia 3201
Phone: +61 3 9708 2317, Fax: +61 3 9708 2318
Email: sales@tritechlubricants.com,
Web: www.tritechlubricants.com,



AUSTRALIAN MADE AND
AUSTRALIAN OWNED