



# SYNERGY 10W60 SN/CF

Code: 9176  
Date: 10-05-2015

## DESCRIPTION

**SYNERGY 10W60** is a full synthetic petrol/diesel motor oil formulated with advanced synthetic base stocks, premium additive and a broad viscosity rating providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals.

**SYNERGY 10W60** is a multi viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts. It also provides protection against wear and corrosion, prevents oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits.

## SUMMARY OF BENEFITS

**SYNERGY 10W60** meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines

**SYNERGY 10W60** is a low ash formulation designed to maintain outstanding engine cleanliness

## SPECIFICATIONS

- API SN
- VW 502.00, 505.00
- ACEA A3/B4
- MB –APPROVAL 229.1
- FORD M2C153-E
- GM 6094M

## TECHNICAL DATA

CHARACTERISTICS	10W60 SN/CF
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	24.9
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	18.9
Viscosity index	170

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS

15 Leah Grove, Carrum Downs, Victoria, Australia 3201  
Phone: +61 3 9708 2317, Fax: +61 3 9708 2318  
Email: [sales@tritechlubricants.com](mailto:sales@tritechlubricants.com),  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com),



AUSTRALIAN MADE AND  
AUSTRALIAN OWNED